

Product Data Sheet

BENTONITE



Crude Wyoming Grade

BENTONITE Crude Wyoming Grade composes specially selected, premium natural sodium-Bentonite and is used in a variety of specialties when superior performance is required.

Advantages

- Versatile natural sodium-Bentonite suitable for a wide range of industrial applications
- Consistent quality through specially selected crude material for reliable performance

Typical Properties

Parameter	Test method / In accordance with	Required
Moisture content	DIN 18121-1	Max. 17%
Grain size	-	< 4 cm/100%
Methylene blue	VDG	Min. 300 mg MB/gr.
Water absorption	Enslin Neff (DIN 18132 MOD)	Min. 600%
Montmorillonite Content	X-ray diffraction	Min. 75%
Colour	-	Beige / grey
Form	-	Granules & powder

BENTONITE Crude Wyoming Grade is available in bulk.

Version; 06-2025

*As far as we can judge, the above information is correct. However, we cannot give you any guarantees about the results you will achieve with this. This description is offered to you on the condition that you decide for yourself to what extent it is suitable for your purposes.

Cebo Holland BV
Westerduinweg 1
NL-1976 B.V. IJmuiden
The Netherlands

info@cebo.com
www.cebo.com
Phone +31(0)255-546262

