

Product Data Sheet

# CEBOGEL®



# Promex

**CEBOGEL® Promex** is a performance enhancing Bentonite-based additive, defined by its impressive absorption capabilities. When mixed with water, CEBOGEL Promex forms a gel-like structure, enabling swelling and promoting effective sealing properties. The product is designed to improve the efficiency of existing ingredients in waterproofing and sealing solutions, ultimately optimizing costs for the end-user.

### Advantages

- Gel-forming swelling behaviour delivering strong and reliable sealing performance
- Enhances efficiency of existing formulations, enabling cost-optimized waterproofing solutions

### Typical Properties

Parameter	Test method / In accordance with	Required
Moisture content	% on wet / Halogen 150°C constant weight	≤ 13%
Grain size	Passing 125 µm dry sieve	≥ 95% < 125 µ
Specific density	-	≈ 2300 kg/m <sup>3</sup>
Bulk density	-	≈ 900 kg/m <sup>3</sup>
Methylene blue	VDG	≥ 300% mg/g
Plate water absorption	ASTM E946-92	≥ 650%

**CEBOGEL® Promex is available in 1000 kg big bags and as bulk.**

**Version; 05-2025**

\*As far as we can judge, the above information is correct. However, we cannot give you any guarantees about the results you will achieve with this. This description is offered to you on the condition that you decide for yourself to what extent it is suitable for your purposes.

**Cebo Holland BV**  
Westerduinweg 1  
NL-1976 B.V. IJmuiden  
The Netherlands

info@cebo.com  
www.cebo.com  
Phone +31(0)255-546262

