

Product Data Sheet

CEBOGEL®



Promex Plus

CEBOGEL® Promex Plus CEBOGEL® Promex Plus is a high-performance bentonite-based additive with superior absorption capacity. As the most advanced product in the CEBOGEL Promex range, it is engineered for maximum uptake. When mixed with water, it forms a gel structure that swells and enhances sealing performance. It improves the efficiency of other components in waterproofing systems, helping to optimize overall cost.

Advantages

- High absorption and swelling capacity, resulting in excellent sealing performance
- Cost efficiency, by enhancing the effectiveness of other components in the formulation

Typical Properties

Parameter	Test method / In accordance with	Required
Moisture content	% on wet / Halogen 150°C constant weight	≤ 13%
Grain size	Passing 125 µm dry sieve	≥ 95% < 125 µ
Specific density	-	≈ 2300 kg/m ³
Bulk density	-	≈ 900 kg/m ³
Methylene blue	VDG	≥ 300% mg/g
Plate water absorption	ASTM E946-92	≥ 800%

CEBOGEL® Promex is available in 1000 kg big bags and as bulk.

Version; v2 2026

*As far as we can judge, the above information is correct. However, we cannot give you any guarantees about the results you will achieve with this. This description is offered to you on the condition that you decide for yourself to what extent it is suitable for your purposes.

Cebo Holland BV
Westerduinweg 1
NL-1976 B.V. IJmuiden
The Netherlands

info@cebo.com
www.cebo.com
Phone +31(0)255-546262

