



## Product Data Sheet

# Cebo F-SEAL

### Industrial Drilling

**Cebo F-SEAL** is an acid-soluble, fibrous lost circulation material, composed of synthetic resin-bound stone wool. Cebo F-SEAL is used as an additive for preventing and resolving loss of circulation in concentrations of up to 20 kg/m<sup>3</sup>. The product's fibrous composition builds a structure against high-permeable formations on which a Bentonite fluid can create a filter cake; this effectively prevents drilling fluids from seeping into the surrounding formation. Cebo F-SEAL is an inorganic, non-fermenting product and can be easily mixed.

#### Advantages

- Easy to mix
- Immediate results
- High performance
- Low mixing ratio

#### Typical Properties

Parameter	Test method / In accordance with	Required	Typical Property
Composition	-	-	Synthetic resin-bound stone wool
Colour	-	-	Tan/brown
Form	-	-	Flocks
Smell	-	-	Odourless

#### Mixing & Application

Cebo F-SEAL can be added directly through a Venturi-Hopper into the mixing system. For normal treatment to the active system, add 3 - 10 kg/m<sup>3</sup> drilling fluid. As a pill, add 10 - 20 kg/m<sup>3</sup> of drilling fluid.

**Cebo F-SEAL is available in 20 kg bags.**

Version; 03-2021

In so far as we can ascertain, the above-stated information is correct. However, we are unable to provide any guarantees with regard to the results that you will achieve with this. This specification is provided on the condition that you determine yourself to what degree it is suitable for your purposes.